

# MASTERMIX



Type		Master 1500	Master 1875	Master 2250	Master 3000	Master 4000	Master 4500	Master 5000
Capacity per batch	kg	1000 L 2400	1250 L 2750	1500 L 3600	2000 L 4800	8/3 m <sup>3</sup> 6000	2000 L 7200	3333 L 8000
Production of precast concrete	m <sup>3</sup> /h.	30	35	45	60	80	90	100
Production of ready-mix concrete	m <sup>3</sup> /h.	50	60	75	90	100	130	150
Motor power	kW	50	57	75	97	119	145	150

# OPTIONS

- Aggregate storage from 4 to 8 compartments from 25 to 100 m<sup>3</sup> per compartment
- Aggregate loading system
- Aggregate discharge system
- Cladding of mixer unit
- Covering of mixer unit
- Ice weigh hopper
- Cleaning system for mixer



# MASTERMIX PROGRESS THROUGH INNOVATION

## MASTERMIX PROGRESS THROUGH INNOVATION

Easy transportation  
Designed for the most extreme conditions



### Jobsite

The compact design enables easy and quick implementation to cope with the widest range of needs.

### Precast

Flexible and fast to install fitting perfectly to your working environment and your production.

### Ready-mix

Optimum operation of high-volume and high-quality concrete. Easy maintenance. Optimum truck circulation.



**SKAKO Concrete**  
Bygmestervej 2 - 5600 Faaborg  
Denmark  
[www.skako.com](http://www.skako.com)

**SKAKO Concrete**  
Parc du Mélantois / Rue des Séquoias  
CS 60438 / 59814 Lesquin Cedex  
France



**SKAKO**  
CONCRETE

# MASTERMIX

THE INNOVATIVE AND  
FUNCTIONAL PLANT  
TAKING CARE OF  
THE ENVIRONMENT AND  
YOUR SAFETY



## ERGONOMICS

Large platform for access around the mixer.  
Anti-skid aluminium tear plates easy to clean.

## ... AND SECURITY

ISO14122-3 standard platforms/ stairs with secured railing.  
Anti-fall safety.  
Floor level access to main maintenance components.



## ENVIRONMENT

Galvanized water weigh hopper for clean or recycled water.  
Sealed cement weigh hopper with decompression vent hose.

## MODULARITY

4 to 8 compartments.  
Storage capacity of 60 to 400 m<sup>3</sup>.  
2 outlet gates or one large discharge gate or activator per compartment.  
Galvanized cement weigh hopper with space for up to 5 screw conveyors.

## COMFORT

Easy access for cleaning/inspection.  
Prepared for automatic cleaning system.  
Bracket/beam to lift up spare/wear parts.  
Flexible and resistant chute.

## SPEED

Fast installation.  
Limited civil engineering.  
Prewired and factory tested.

## MOBILITY

Easy to dismantle and transport.  
Meets EU road standards.  
Rear axle and signal devices.

## PRODUCTIVITY

The control system optimizes the performance of the plant for all applications.

# ADD-ONS

TO SIMPLIFY  
YOUR PRODUCTION



1000 kg  
bracket/beam



Tool set  
provided



Cladding



Base cone  
section for  
complete  
discharge



Separate  
hydraulic  
power pack



Electro  
valve box